

# TAPCO-INTEGRATED BLINKERSIGN®

## Ruggedized

### SPECIFICATIONS

<b>POWER</b>	Low voltage, current controlled through TAPCO controller
<b>SIGN LEGEND</b>	Various MUTCD options available
<b>SIGN SUBSTRATE</b>	Front plate: Extra thick 0.10" aluminum Back plate: Standard 0.080" aluminum
<b>HIGH DENSITY POLYETHYLENE SUBSTRATE</b>	Extra thick 0.750" HDPE substrate with routed enclosed channels to protect LEDs and wiring
<b>REFLECTIVE SHEETING</b>	3M™ DG3 with anti-graffiti overlay
<b>DIMMING</b>	Variable based on photocell sensor input
<b>FLASH PATTERN</b>	Various MUTCD-compliant options dependent upon sign legend
<b>LED TYPE</b>	Environmentally-sealed, high-power 1 watt LED
<b>LED COLOR</b>	Amber, red, white or orange
<b>LED QUANTITY</b>	Various options dependent upon sign legend
<b>LED LIFE EXPECTANCY</b>	100,000 hours
<b>VISIBILITY</b>	Daytime: more than 1,000 feet Nighttime: more than 1 mile
<b>MOUNTING BRACKETS</b>	Z-bar standard. Single post and double post available.
<b>OPERATING TEMPERATURE RANGE</b>	-40°F to 122°F (-40°C to 50°C)
<b>DIMENSIONS</b>	Various options dependent upon sign legend

